

2SA608(K)

/ Descriptions


TO-92 PNP

/ Features

2SA608(K) SP NP

/ Applications

/ Equivalent Circuit



/ Pinning





/ hFE Classifications & Marking

| | | | | |
|--|--|--|--|--|
| | | | | |
| | | | | |


/ Absolute Maximum Ratings(Ta=25)

| | | | |
|--|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

/ Electrical Characteristics(Ta=25)

| | | | | | | |
|--|--|---|--|--|--|---|
| | | | | | | |
| | | | | | | μ |
| | | | | | | μ |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | |  <p>开关时间测试电路</p> | | | | |
| | |  <p>开关时间测试电路</p> | | | | |


/ Electrical Characteristic Curve




/ Package Dimensions

TO-92

Unit: mm




/ Marking Instructions



BR:
A608
D:

() / Temperature Profile for Dip Soldering(Pb-Free)



± ± ± ±

/ Resistance to Soldering Heat Test Conditions

± ±

/ Packaging SPEC.

| 封装形式 | 包装数量 | | | | | 包装尺寸 : | | |
|-------|------------------|-----------------------|------------------------|------------------------------|------------------------|---------|-------------|-------------|
| | Units/Bag 只/袋 | Bags/Inner Box 袋/盒 | Units/Inner Box 只/盒 | Inner Boxes/Outer Box 盒/箱 | Units/Outer Box 只/箱 | Bag 袋 | Inner Box 盒 | Outer Box 箱 |
| TO-92 | 1,000 | 10 | 10,000 | 5 | 50,000 | 135×190 | 237×172×102 | 560×245×195 |
| | 1,000 | 10 | 10,000 | 10 | 100,000 | 135×190 | 237×172×102 | 560×245×375 |

| 封装形式 | 包装数量 | | | | | 包装尺寸 : | |
|-------|--------------------|------------------------|-------------------------|------------------------------|------------------------|-------------|-----------------------------------|
| | Units/tape 只/纸带 | Tape/Inner Box 纸带/盒 | Rows/Inner Box 纸带层/盒 | Inner Boxes/Outer Box 盒/箱 | Units/Outer Box 只/箱 | Inner Box 盒 | Outer Box 箱 |
| TO-92 | 3,000 | 1 | 120 | 10 | 30,000 | 328×230×42 | 小箱 480×346×235, 大箱 547×407×268 |

/ Notices