


--	--	--	--	--	--

F



Rev.A Aug.-2022

描述

SOT-23

Silicon Diode in a SOT-23 Plastic Package.

特征


AEC-Q101

Fast Switching, High Conductance, Qualified to AEC-Q101 Standards for High Reliability, HF Product.


用途

Small signal diode, Meet the stringent requirements of automotive applications.

内部等效电路




引脚排列




PIN: See Equivalent Circuit.

印章代码

Type	BRMMBD4148Q	BRMMBD4148SEQ	BRMMBD4148CCQ	BRMMBD4148CAQ
Marking	Q5H	QD4	QD5	QD6





Parameter	Symbol	Rating	Unit
Repetitive Reverse Voltage	V_{RRM}	100	V
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Non-repetitive Peak Forward Surge Current	$I_{FSM}(PW=1.0S)$	1.0	A
Non-repetitive Peak Forward Surge Current	$I_{FSM}(PW=1.0\mu S)$	2.0	A
Power Dissipation	PC	350	mW
Thermal Resistance, Junction to Ambient	R_{JA}	357	$^{\circ}C/W$
Junction Temperature	T_j	150	$^{\circ}C$
Storage Temperature			




Rev.A Aug.-2022

电参数曲线图





印章说明



Q


5H

Note:

Q: Automobile halogen-free product Code

5H: Product Type

Rev.A Aug.-2022



回流焊温度曲线图 无铅 Temperature Profile for IR Reflow Soldering(Pb-Free)