

/ Descriptions

TO-126 NPN Silicon NPN transistor in a TO-126 Plastic Package.


/ Features

TIP127L
Complement to TIP127L.

/ Applications

Medium power linear switching applications.

/ Equivalent Circuit



/ Pinning








PIN1 Emitter PIN 2 Collector PIN 3 Base

/ h_{FE} Classifications & Marking

See Marking Instructions.


/ Electrical Characteristic Curve




/ Package Dimensions

T0-126

单位: mm



/ Marking Instructions



BR

TIP122

L: TO-126

Note:


BR: Company Code

TIP122: Product Type.

L: TO-126 Package

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | | 2.Peak Temp.:255±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5